



Product Service

CERTIFICATE

No. Z2 082429 0132 Rev. 06

Model(s):

RSM72-6-xxxMDG, xxx=315 to 385 in step of 5
 RSM60-6-xxxMDG, xxx=265 to 320 in step of 5
 RSM144-6-xxxMDG, xxx=350 to 405 in step of 5
 RSM132-6-xxxMDG, xxx=320 to 370 in step of 5
 RSM120-6-xxxMDG, xxx=295 to 340 in step of 5
 RSM72-6-xxxBMDG, xxx=340 to 385 in step of 5
 RSM60-6-xxxBMDG, xxx=280 to 325 in step of 5
 RSM144-6-xxxBMDG, xxx=360 to 405 in step of 5
 RSM132-6-xxxBMDG, xxx=330 to 370 in step of 5
 RSM120-6-xxxBMDG, xxx=300 to 340 in step of 5
 xxx is standing for rated output power at STC

Parameters:

Construction:	Frameless or framed, double glass with Junction box, Cable and Connectors.
Safety Class :	Class II
Maximum System Voltage:	1500 V DC
Fire Safety Class:	Class A according to UL790
Test Laboratory:	Yangzhou Opto-Electrical Products Testing Institute, No. 10 West Kaifa Road, Yangzhou, 225009 Jiangsu, P. R. China.

Tested according to:

IEC 61215-1(ed.1)
 IEC 61215-1-1(ed.1)
 IEC 61215-2(ed.1)
 IEC 61730-1(ed.2)
 IEC 61730-2(ed.2)
 EN 61215-1:2016
 EN 61215-1-1:2016
 EN 61215-2:2017
 EN IEC 61730-1:2018
 EN IEC 61730-1:2018/AC:2018-06
 EN IEC 61730-2:2018
 EN IEC 61730-2:2018/AC:2018-06

Production Facility(ies):

082429, 094163, 101449

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT